

WHY A GEL?

RUST ISN'T ALWAYS ON THE FLOOR

Thin rust removers run straight off a gate, a chassis rail or a bolt head before they get to work. Rust Dissolver is thickened to **cling** – it stays put on vertical, sloped and overhead steel and keeps working exactly where you put it.



SPRAY ON

Trigger bottle applies it fast and even – no decanting, no brushes needed.



CLINGS TO THE SURFACE

Gel body holds on the vertical and the underside instead of running to the ground.



WORKS FAST

Light to medium rust is gone in 30 minutes or less. Heavy scale takes a second coat.

Rust doesn't knock off at five. Neither does this.



TURN FOR HOW IT WORKS →



RUST OFF – AND KEPT OFF

RUST DISSOLVER · GEL FORMULA · SOUTH AFRICA

WHERE IT EARNS ITS KEEP

TOOLS & HARDWARE	spanners, clamps, blades, bolts
AUTOMOTIVE	brake parts, chassis, trailers, tow bars
GATES & RAILINGS	burglar bars, palisade, balustrades
GALVANISED SHEET	rust bloom · also etches new galv
BATHROOMS	lime, calcium & hard-water stains

Available at leading paint & hardware retailers across South Africa.

- One-step rust **remover + inhibitor**
- Spray, brush or dip – **stays where you put it**
- Rinse clean, **paint within the hour**, water clean-up

[STOCKIST LOCATOR
rust-oleum.co.za]

[QR]

Contains phosphoric acid – eye and skin irritant. Always read the label and the Technical Data Sheet before use. Do not use on marble; do not let the product dry on painted surfaces; buff aluminium and chrome dry after rinsing. Colours and results shown are a guide only. Distributed in South Africa by [DISTRIBUTOR NAME]. © 2026 Rust-Oleum. RUST-OLEUM® is a registered trademark. [Rust-Oleum South Africa · address · tel · email]



REMOVES RUST · INHIBITS RUST

RUST DISSOLVER

GEL FORMULA

Water-based · trigger spray, brush or dip

One pass lifts the rust off bare metal – then leaves crystals behind that stop it coming back.

1 QT · 946 ML · SKU 300112



HOW IT WORKS

DISSOLVE. INHIBIT. ONE STEP.

A water-based chemical action, not a wire brush.

1 PENETRATES

The water-based gel soaks into the pits and voids in the rusted surface.

2 DISSOLVES

Phosphoric chemical action breaks rust and oxidation down – and stops at the sound metal underneath.

3 INHIBITS

Micro rust-inhibiting crystals form and bond with the surface molecules of the metal, resisting new rust.

Up to 12 months

bare-metal protection – let it dry on the surface instead of rinsing it off.



RUSTED



CLEAN & SEALED

HOW TO USE IT

AS A REMOVER

1. **Degrease** the metal, then rinse to break the surface tension and wash off loose dirt.
2. **Apply** by spray, brush or dip – enough to wet the rust right through.
3. **Keep it wet.** Light-medium rust clears in 30 min or less; heavy scale may need a second application.
4. **Rinse or wipe** clean. Wait at least 1 hour before painting.

AS A RUST INHIBITOR

Once the rust is gone, let it dry on the bare metal instead of rinsing – protects for up to 12 months.

BETTER PAINT ADHESION

On clean metal, dilute 50/50 with water, apply, then rinse or wipe before painting.

NEW GALVANISED METAL

Apply, leave 3-5 minutes, wipe clean – etches the surface ready for paint.

HEAVY SCALE

Knock off loose flakes with a wire brush first, then let the gel work the rest.

BATHROOM BONUS

Also lifts lime, calcium & hard-water stains from porcelain, tile, fibreglass and glass – spray on, wait 5 minutes, agitate with a brush, rinse.

Don't: let it dry on painted surfaces · use on marble · leave aluminium or chrome unrinsed – rinse and buff dry.

WHERE IT WORKS

SURFACES

IRON & STEEL

dissolves rust & oxidation

CHROME & ALUMINIUM

apply wet, rinse, buff dry

GALVANISED

rust bloom · etches new galv

PORCELAIN, TILE, GLASS

lime & hard-water stains

AUTO COOLING SYSTEMS

circulate, then flush

SPEC

PACK

946 mL (1 QT) trigger · SKU 300112

FORM

water-based thixotropic gel

APPLY BY

spray · brush · roller · dip

WORKING TIME

30 min (light-medium rust)

HEAVY RUST

second application

BEFORE PAINTING

rinse · wait ≥ 1 hr

BARE-METAL PROTECTION

up to 12 months (allow to dry)

CLEAN-UP

water

CAUTION

contains phosphoric acid

ALSO FROM RUST-OLEUM

Stops Rust® enamels · Rust Reformer · Self-Etching Primer